

# Platinum SLIM



F-90 SL



F-60 SL



LCR-60 SL

	<b>F-90 SL</b>	<b>F-60 SL</b>	<b>LCR-60 SL</b>
Speaker Type	Floorstanding	Floorstanding	Left / Center / Right
Drivers Configuration	Tweeter 25mm (1") TPTTD, TWG, TTP  Midrange 133mm (5.25") TPACD  Bass 3 x 133mm (5.25") 2 x TPACD, 1 x TPAPR	Tweeter 25mm (1"), TPTTD, TWG, TTP  Bass / Midrange 4 x 102mm (4") TPACD	Tweeter 25mm (1") TPTTD, TWG, TTP  Bass / Midrange 4 x 102mm (4") TPACD
Recommended Amplifier Power	20 - 240W	20 - 150W	20 - 150W
Sensitivity	91dB	90dB	89dB
Crossover Points	700Hz 3.7kHz	450Hz 2.5kHz	450Hz 2.5kHz
Impedance	6ohm	6ohm	6ohm
Frequency Response	31Hz - 40kHz	35Hz - 40kHz	39Hz - 40kHz
Dimensions (H x W x D)	103.5 x 17 x 24.5 cm	98.5 x 15.5 x 23.7 cm	13.5 x 76 x 11 cm
Net Weight	32.6 kg / pair	26.4 kg / pair	8.5 kg / pc
Finishes		Black High Gloss White	Wenge High Gloss Black
			Walnut Matt Black

Floorstanding models: The height excluding spikes and including a base. The weight including a base.  
\*Weights for PVC finish versions.