

# Platinum V.2



F-120 v.2



F-100 v.2



F-60 v.2



SW-10 v.2

	Platinum F-120 v.2	Platinum F-100 v.2	Platinum F-60 v.2	Platinum SW-10 v.2
Speaker Type	Floorstanding	Floorstanding	Floorstanding	Active Subwoofer
Drivers Configuration	Tweeter 25mm (1") TPTTD, TWG, TTP  Midrange 133mm (5.25") TPACD  Bass 3 x 165mm (6.5") 2 x TPACD, 1 x TPAPR	Tweeter 25mm (1") TPTTD, TWG, TTP  Midrange 133mm (5.25") TPACD  Bass 2 x 165mm (6.5") TPACD	Tweeter 25mm (1") TPTTD, TWG, TTP  Midrange 133mm (5.25") TPACD  Bass 165mm (6.5"), TPACD	Bass 255mm (10") THAW, TSAC
Recommended Amplifier Power	20 - 280W	20 - 250W	20 - 230W	Built-in amplifier, 175W RMS 550W Dynamic Peak, THCA
Sensitivity	93dB	92dB	90dB	
Crossover Points	700Hz 4kHz	700Hz 4kHz	700Hz 4kHz	
Impedance	6ohm	6ohm	6ohm	
Frequency Response	28Hz - 40kHz	30Hz - 40kHz	35Hz - 40kHz	20Hz - 200Hz
Dimensions (H x W x D)	117 x 25 x 34 cm	108.9 x 25 x 34 cm	96.6 x 25 x 34 cm	43 x 35 x 41 cm (incl. feet)
Net Weight	49.2 kg / pair	40.2 kg / pair	36.4 kg / pair	26.5 kg / pc
Finishes		Black High Gloss White	Wenge High Gloss Black	

Floorstanding models: The height excluding spikes and including a base. The weight including a base.  
\*Weights for PVC finish versions.